

Pompe cu lobi seria B

PUMP MODEL	THEORETIC CAPACITY	MAXIMUM SPEED	MAXIMUM POWER	MAXIMUM OPERATING PRESSURE (bar)					STANDARD CONNECTIONS	
				ROTORS WITH ST STANDARD CLEARANCES AND WITH SHAFTS IN		ROTORS WITH SM INCREASED CLEARANCES AND WITH SHAFTS IN		HIGH PRESSURE VERSION: SHAFTS IN DUPLEX AND ANTISEIZURE ALLOY ROTORS		
	l/h/100 RPM	RPM	kW	AISI 316 L	DUPLEX	AISI 316 L	DUPLEX		DN	INCHES
B100	3	1400	1.5	7	10	-	-	-	25	1"
B105	7	1000	4	10	13	15	18	-	40	1" ½
B110	12	1000	4	10	13	15	18	20	40	1" ½
B115	18	1000	5.5	7	10	12	15	-	40	1" ½
B215	23	950	7.5	10	13	15	18	20	40	1" ½
B220	34	950	7.5	7	10	12	15	-	50	2"
B325	55	720	18.5	10	13	15	18	20	65	2" ½
B330	70	720	18.5	7	10	12	15	-	80	3"
B390	90	720	18.5	5	7	10	12	-	80	3"
B430	116	600	30	10	13	15	18	20	80	3"
B440	155	600	30	7	10	12	15	-	100	4"
B470	240	500	45	10	13	15	18	20	100	4"
B490	330	500	45	7	10	12	15	-	100	4"
B550	400	500	45	5	-	7	-	-	125	5"
B660	700	500	75	7	-	-	-	-	150	6"
B680	1050	500	75	4	-	-	-	-	200	8"

